

GLASSWASHER GP-35 230/50/1 DD

Rack size 350x350mm and door clearance 240 mm.

P/N 1303033



√ Easy access to components for repair.

NCLUDES

√ Peristaltic Detergent Pump

ACCESSORIES

- Stands for glass- and dishwashers
- Manual water softeners
- □ Automatic water softeners□ 350X350 mm. baskets
- □ Ø360 / Ø380 mm. baskets
- ☐ Inserts & supplements
- High Feet Kit
- □ Reverse Osmosis device OS-140P

SALES DESCRIPTION

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ Upper and lower washing.
- ✓ Construction in stainless steel AISI 304 2B.
- √ Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

✓ Maximum protection of the washing pump.

Double-walled door

 Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

- √ GP Xperience: simple and intuitive use.
- Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Electronic control panel with IP65 humidity protection.
- √ 100% Tested.

Tech-friendly

√ Tool-free extraction of diffusers and filters for maintenance and cleaning





20720 Azkoitia, Spain



sales@sammic.com



| Project | Date |
|---------|------|
| Item | Qty |

ANI CAG-SSA IC - AHRAMMSSA IC IAIC

product sheet updated 03/09/2021



GLASSWASHER GP-35 230/50/1 DD

Rack size 350x350mm and door clearance 240 mm.

P/N 1303033

SPECIFICATIONS

Basket dimensions: 350 mm x 350 mm Maximum glass height: 240 mm

Cycle duration: 90 " / 120 " / -- "
Production baskets/hour: 45 / 30 / --

Boiler capacity: 3.2 | Wash tank capacity: 12.7 | Water consumption/cycle: 2.2 |

Loading

- √ Pump: 75 W / 0.1 Hp
- √ Tank: 1200 W
- √ Boiler: 2500 W
- ✓ Total loading: 2575 W

Electrical supply: $230 \, \text{V} / 50 \, \text{Hz} / 1 \sim (11.2 \, \text{Mz})$

A)

External dimensions (WxDxH)

- √ Width:420 mm
- √ Depth: 495 mm
- ✓ Height: 645 mm

Net weight: 30 Kg Noise level (1m.): -- dB(A)

Crated dimensions

485 x 590 x 690 mm Gross weight: 33 Kg.



Polígono Basarte, 1. pho 20720 Azkoitia, Spain





| Project | Date |
|---------|------|
| Item | Qty |