



Rack size 500x500mm and door clearance 260 mm

P/N 1303162



SALES DESCRIPTION

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- \checkmark THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ Upper and lower washing.
- ✓ Construction in stainless steel AISI 304 2B.
- \checkmark Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

 \checkmark Maximum protection of the washing pump.

Double-walled door

 Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

- ✓ GP Xperience: simple and intuitive use.
- \checkmark Dedicated cycles: selection of the ideal washing programme using icons.
- \checkmark Electronic control panel with IP65 humidity protection.
- √ 100% Tested.

Tech-friendly

 \checkmark Tool-free extraction of diffusers and filters for maintenance and cleaning



NCLUDES

✓ Peristaltic Detergent Pump

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Maximum glass height: 260 mm

Cycle duration: 90 " / 120 " / -- " Production baskets/hour: 45 / 30 / --

Boiler capacity: 4.5 | Wash tank capacity: 23 | Water consumption/cycle: 2.7 |

Loading

- Pump: 500 W / 0.75 Hp
- √ Tank: 1800 W
- ✓ Boiler: 2500 W
- ✓ Total loading: 3000 W

Electrical supply: 230 V / 50 Hz / 1 ~ (13 A)

External dimensions (WxDxH)

- √ Width:580 mm
- ✓ Depth: 630 mm
- ✓ Height: 710 mm
- Net weight: 52 Kg Noise level (1m.): -- dB(A)

ACCESSORIES

- Stands for glass- and dishwas-
- hers

 Manual water softeners
- Automatic water softeners
- Inserts & supplements
 High Feet Kit
 - Reverse Osmosis device OS-140P
- □ 500 x 500 mm. baskets

WARE WASHING



Sammic | www.sammic.com Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
Annual	

Approved

product sheet updated 03/09/2021