#### **UTENSIL WASHER UX-600**

Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing



Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 650 mm

Cycles: 5

Cycle duration: //

Production baskets / hour: //

Pressure pump power:

Electrical connection:

#### Loading

- √ Pump: 3 Hp / 2200 W
- √ Tank: 6000 W
- ✓ Boiler: 9000 W
- √ Total loading: 11200 W

Feed water temperature: 10°C - 60°C Wash temperature: 40°C - 70°C Rinse temperature: - 87°C Wash tank capacity: 55 I Boiler capacity: 12 I

Water consumption/cycle: 3.5 I

Drainage base maximum height: 185 mm

Drain diameter: 30 mm

#### External dimensions (W x D x H)

- √ Width:742 mm
- ✓ Depth (closed):852 mm
- ✓ Depth (open):1232 mm
- √ Height (closed):1843 mm
- √ Height (open):2035 mm

Net weight: 168 kg Noise level (1m.): 76 dB(A)

Crated dimensions 790 x 980 x 1950 mm

1303501

1303505

**AVAILABLE MODELS** 

Utensil washer UX-600 230-400/50/3N DD

1303506 Utensil washer UX-600C 230-400/50/3N SB DD

UX-600C 230-400/50/3N DD

1303508 UX-600BC 230-400/50/3N DD

\* Ask for special versions availability

#### SALES DESCRIPTION

#### Ideal to wash big sized pots and wares.

- √ Powerful and high pressure: specially indicated for restaurants, icecream shops, pastries and butcheries.
- Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- √ Double skinned machines: silent working and reduced thermical dispersions.
- √ Wash tank without corners to avoid dirt accumulation in angles.
- √ Stamped wash dispersers in stainless steel tubes.
- √ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- √ Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- Reduced water consumption.

#### **NCLUDES**

- √ 1 stainless steel basket and insert for 4 trays.
- √ Adjustable detergent dosing equipment.

#### **OPTIONAL**

- Stainless basket.
- Stainless carrier for trays.

#### **Accessories**

- Stainless steel baskets ■ Manual water softeners
- Dosing equipments Carrier for trays
- Automatic water softeners

#### **SPECIFICATIONS**

Basket dimensions: 600 mm x 630 mm





# WARE WASHING

## product sheet updated 14/02/2025



### **UTENSIL WASHER UX-600**

Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing system.

Sammic | www.sammic.com
Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty

Approved