# product sheet updated 12/02/2025



### **UTENSIL WASHER UX-750**

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system.



Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 820 mm

Cycles: 5

Cycle duration: //

Production baskets / hour: //

Pressure pump power:

Electrical connection:

#### Loading

- ✓ Pump: 3,2 Hp / 2400 W
- ✓ Tank: 6000 W
- ✓ Boiler: 9000 W
- √ Total loading: 11400 W

Feed water temperature: 10°C - 60°C Wash temperature: 40°C - 70°C Rinse temperature: 70°C - 87°C Wash tank capacity: 75 | Boiler capacity: 12 | Water consumption/cycle: 4 |

Drainage base maximum height: 185 mm

Drain diameter: 30 mm

#### External dimensions (W x D x H)

- √ Width:922 mm
- ✓ Depth (closed):932 mm
- ✓ Depth (open):1400 mm
- √ Height (closed):2015 mm
- √ Height (open):2300 mm

Net weight: 216 kg Noise level (1m.): 76 dB(A)

## SALES DESCRIPTION

#### Ideal to wash big sized pots and wares.

- Powerful and high pressure: specially indicated for restaurants, icecream shops, pastries and butcheries.
- Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- Double skinned machines: silent working and reduced thermical dispersions.
- √ Wash tank without corners to avoid dirt accumulation in angles.
- ✓ Stamped wash dispersers in stainless steel tubes.
- ✓ Easy to remove wash- and rinse dispersers.
- Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- ✓ Reduced water consumption.

# **AVAILABLE MODELS**

1303520 UX-750C 230-400/50/3N DD

1303525 UX-750BC 230-400/50/3N DD

1303521 UX-750C 220/60/3 DD

\* Ask for special versions availability

#### INCLUDES

√ 1 stainless steel basket and insert for 4 trays. Adjustable detergent dosing equipment.

#### **OPTIONAL**

Stainless basket.

☐ Stainless carrier for trays.

#### **Accessories**

- ☐ Stainless steel baskets
- Dosing equipments
- Manual water softeners
- □ Carrier for trays
- Automatic water softeners

#### **SPECIFICATIONS**

Basket dimensions: 780 mm x 700 mm





# WARE WASHING



# **UTENSIL WASHER UX-750**

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system.

Sammic | www.sammic.com
Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



	Project	Date
	Item	Qty

Approved